



# CITY

## ISOTHERM / REFRIGERATED

**LIGHT RANGE** - Up to 7.000 kg. MAM



### General information:

#### PANELS

Description	Thickness
Lateral	75 mm
Roof	75 mm
Frontal	75 mm
Rear	73 mm
Floor	95 mm

- Up to 7.000 kg MAM.
- Perfect for combining road urban distribution with positive temperatures and refrigerated.
- Assembling system with bicomponent polyurethanic adhesive.
- Different floor finishing possibilities.
- Pultrusion external mouldings.
- Stainless steel hinges and door locks container type.
- Aluminium or polyester skirting board.

### Optional

- LED interior lights integrated at roof with movement sensor.
- Roll Up rear door.
- Trunking for second evaporator.
- Interior strip protection inox or aluminium.
- Cargo rail (inox or galvanised).
- Fixed or movable division.
- Side door (single or double).
- Aluminium finishing floor.
- Waterdrain with valve.
- Elongation of rear frame for fork lifts entrance.
- Aluminium or steel chassis subframe.
- Aluminium or stainless steel protection strips for rear doors.
- 1 or 3 flaps rear door.
- Ventilation windows.
- Tail lift bottom runner on the rear frame.

### Accessories

- PVC curtains.
- Tail lifts.
- Refrigeration equipment.
- Tool boxes.
- Plastic extinguisher boxes.
- Pull down rear step.
- Aluminium anti cycling profiles.
- Thermo plastic mudguards and flaps.
- Spoilers.
- Thermographs.