



HIGH WAY

ISOTHERM / REFRIGERATED

HEAVY RANGE - Up to 26.000 kg. MAM



General information:

PANELS

Description	Thickness
Lateral	65/50 mm
Roof	85 mm
Frontal	105 mm
Rear	73 mm
Floor	140 mm

- Up to 26.000 kg MAM.
- Design and aesthetic for the long distance transport.
- Screwed assembling system.
- Aluminium outer profiles.
- Inox rear frame with integrated hinges and round shape front wall.
- Aluminium skirting board 8 mm thickness for high resistance and waterproof.

Optional

- LED interior lights integrated at roof with movement sensor.
- Roll Up rear door.
- Trunking for second evaporator.
- Interior strip protection inox or aluminium.
- Cargo rail (inox or galvanised).
- Fixed or movable Division.
- Side door (single or double).
- Aluminium finishing floor.
- Waterdrain with valve.
- Elongation of rear frame for fork lifts entrance.
- Aluminium or steel chassis subframe.
- Aluminium or stainless steel protection strips for rear doors.
- Integrated hinges at rear frame.
- 1, 3 or 4 flaps rear door.
- Ventilation windows.
- Tail lift bottom runner on the rear frame.

Accessories

- PVC curtains.
- Tail lifts.
- Refrigeration equipment.
- Tool boxes.
- Plastic extinguisher boxes.
- Pull down rear step.
- Aluminium anti cycling profiles.
- Thermo plastic mudguards and flaps.
- Spoilers.
- Thermographs.