



# ROAD

## ISOTHERM / REFRIGERATED

**LIGHT RANGE** - Up to 15.000 kgs. MAM



### General information:

#### PANELS

Description	Thickness
Lateral	65 mm
Roof	85 mm
Frontal	85 mm
Rear	73 mm
Floor	110 mm

- Up to 15.000 kg MAM.
- Perfect for medium and long distance transport for perishables products.
- Combined assembling system screwed and bicomponent polyurethanic adhesive.
- Aluminium & polyester outer profiles.
- Inner perimeter reinforced with aluminium profiles.
- Inox hinges and door locks container type.
- Aluminium skirting board.

### Optional

- LED interior fitting roof lights integrated at roof wth movement sensor.
- Roll Up rear door.
- Trunking for second evaporator.
- Pull down step protection (inox or galvanised).
- Cargo rail (inox or galvanised).
- Fixed or movable division.
- Side door (single or double).
- Aluminium finishing floor.
- Waterdrain with valve.
- Elongation of rear frame for fork lifts entrance.
- Aluminium or steel chassis subframe.
- Aluminium or inox protection strips for rear doors.
- Integrated hinges at rear frame.
- 1 or 3 flaps rear door.
- Ventilation windows.
- Tail lift bottom runner on the rear frame.

### Accessories

- PVC curtains.
- Tail lifts.
- Refrigeration equipment.
- Tool boxes.
- Plastic extinguisher boxes.
- Pull down rear step.
- Aluminium anti cycling profiles.
- Thermo plastic mudguards and flaps.
- Spoilers.
- Thermographs.